

GS/L RA 30S4 1150X685

EASY TO MOVE



Description

| | | | |
|----------------------------|---|----|------------|
| 1.1 Manufacturer | | | LIFTER |
| 1.3 Drive | | | Manual |
| 1.4 Operator type | | | Pedestrian |
| 1.5 Load capacity | Q | Kg | 3000 |
| 1.6 Load centre distance | c | mm | 600 |
| 1.8 Load axle to end forks | x | mm | 932 |
| 1.9 Wheel base | y | mm | 1192 |

Weights

| | | | |
|------------------------------|--|----|------|
| 2.1 Service weight | | Kg | 93 |
| 2.2 Axle load, laden rear | | Kg | 2198 |
| 2.2 Axle load, laden front | | Kg | 895 |
| 2.3 Axle load, unladen front | | Kg | 62 |
| 2.3 Axle load, unladen rear | | Kg | 31 |

Tyres/Chassis

| | | | |
|----------------------------------------------|-----|----|-------------------|
| 3.1 Tyres: front wheels | | | POLY.I./ NYLON |
| 3.1 Tyres: rear wheels | | | NYLON |
| 3.2 Tyre size: Steering wheels - Diameter | | mm | 200 |
| 3.2 Tyre size: Steering wheels - Width | | mm | 55 |
| 3.3 Tyre size: Load rollers - Diameter | | mm | 82 |
| 3.3 Tyre size: Load rollers - Width | | mm | 60 |
| 3.5 Tyre size: rear wheels - Q.ty (X=driven) | | nr | 4 |
| 3.5 Rear balancing axle | | | No |
| 3.6 Tread, front | b10 | mm | 155 |
| 3.7 Tread, rear | b11 | mm | 535 |

Dimensions

| | | | |
|--------------------------------------------|-----|----|------|
| 4.4 Lift height | h3 | mm | 115 |
| 4.9 Height of tiller in drive position max | h14 | mm | 1160 |
| 4.15 Height, lowered | h13 | mm | 85 |
| 4.19 Overall length | l1 | mm | 1550 |
| 4.20 Length to face of forks | l2 | mm | 400 |
| 4.21 Overall width | b1 | mm | 685 |
| 4.22 Fork dimensions - Thickness | s | mm | 50 |
| 4.22 Fork dimensions - Width | e | mm | 150 |
| 4.22 Fork dimensions - Length | l | mm | 1150 |
| 4.25 Distance between fork arms | b5 | mm | 685 |
| 4.32 Ground clearance, centre of wheelbase | m2 | mm | 35 |
| 4.34 Aisle width | Ast | mm | 1835 |
| 4.35 Turning radius | Wa | mm | 1367 |

Performance data

| | | |
|---------------------------|---------|----|
| 5.2 Lifting speed laden | strokes | 13 |
| 5.2 Lifting speed unladen | strokes | 13 |

*Available accessories: tandem rollers, polyurethane rollers (as a standard on Premium), rubber guide wheels, manual control brake

